

# Fire Extinguishers **Cherwell Fire Safety**

## Water



### Water Extinguishers

- Fully CE Marked
- Manufactured in accordance with BS EN3
- Plastic base for protection
- Fire Rating certified by Lloyds Register
- Impressive 34A rating on Compact 34 model
- Corrosion resistant finish
- Fully polyethylene lined
- Full range of spare parts available

## Foam



### Foam Extinguishers

- Fully CE Marked
- Manufactured in accordance with BS EN3
- Plastic base for protection\*
- Fire test certified by Lloyds Register
- Corrosion resistant finish
- Full range of spare parts available
- Full polyethylene lined

\* excludes 2 litre model

## Specification

Type	WS EX6	WS EX9	WS EX6A	FS EX2	FS EX6	FS EX9
Capacity (ltr)	6	9	6	2	6	9
Fire rating	13A	21A	34A	8A/34B	13A/113B	21A/183B
Extinguishing medium	Water	Water	Water + additive	AFF Foam	AFF Foam	AFF Foam
Working pressure	14 bar	14 bar	14 bar	14 bar	14 bar	14 bar
Temperature (°C)	0 - +60	0 - +60	0 - +60	0 - +60	0 - +60	0 - +60
Cylinder material	Steel	Steel	Steel	Steel	Steel	Steel
Pressurising gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen

checkfire!

# Fire Extinguishers **Cherwell Fire Safety**

## Dry powder



### Dry Powder Extinguishers

- Fully CE Marked
- Manufactured in accordance with BS EN3
- Plastic base for protection\*
- Fire test certified by Lloyds Register
- Corrosion resistant finish
- Full range of spare parts available

\* excludes 2kg model

## Co2



### CO2 Extinguishers

- Fully CE Marked
- Manufactured in accordance with BS EN3
- Aluminium cylinder
- Powder coated corrosion resistant finish
- Supplied with horn and bracket

## Specification

Type	DP EX2	DP EX3	DP EX4	DP EX6	DP EX9	CO EX2	CO EX5
Capacity (ltr)	2	3	4	6	9	2kg	5kg
Fire rating	13A/70B	13A/89B	21A/113B	34A/183B	43A/233B	34B	70B
Extinguishing medium	ABC 40	ABC 40	ABC 40	ABC 40	ABC 40	CO2	CO2
Working pressure	14 bar	14 bar	14 bar	14 bar	14 bar	56 bar @ 20C	56 bar @ 20C
Temperature (°C)	-20 - +60	-20 - +60	-20 - +60	-20 - +60	-20 - +60	-20 - +60	-20 - +60
Cylinder material	Steel	Steel	Steel	Steel	Steel	Aluminium	Aluminium
Pressurising gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	-	-

checkfire!

# Fire Extinguishers **Cherwell Fire Safety**

## Water



### Polished Stainless Steel Water Extinguishers

- Fully CE Marked
- Plastic base for protection
- Fire Rating certified by Lloyds Register
- Superb polished finish
- Stainless steel cylinder
- Full range of spare parts available

## Foam



### Polished Stainless Steel Foam Extinguishers

- Fully CE Marked
- Plastic base for protection
- Fire Rating certified by Lloyds Register
- Superb polished finish
- Stainless steel cylinder
- Full range of spare parts available

## Specification

Type	WS EX6/SS	WS EX9/SS	WS EX6A/SS	FS EX6/SS	FS EX9/SS
Capacity (ltr)	6	9	6	6	9
Fire rating	13A	21A	34A	13A/113B	21A/183B
Extinguishing medium	Water	Water	Water + additive	AFF Foam	AFF Foam
Working pressure	14 bar	14 bar	14 bar	14 bar	14 bar
Temperature (°C)	0 - +60	0 - +60	0 - +60	0 - +60	0 - +60
Cylinder material	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Pressurising gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen

# Fire Extinguishers **Cherwell Fire Safety**

## Dry Powder



### Polished Stainless Steel Powder Extinguishers

- Fully CE Marked
- Plastic base for protection
- Fire Rating certified by Lloyds Register
- Superb polished finish
- Stainless steel cylinder
- Full range of spare parts available

## CO2



### Polished Alloy CO2 Extinguishers

- Fully CE Marked
- Fire Rating certified by Lloyds Register
- Superb polished alloy cylinder
- Supplied with horn and bracket

## Specification

Type	DP EX6/SS	DP EX9/SS	CO EX2/P	CO EX5/P
Capacity (kg)	6	9	2	5
Fire rating	34A/183B	43A/233B	34B	70B
Extinguishing medium	ABC 40	ABC 40	CO2	CO2
Working pressure	14 bar	14 bar	56 bar @ 20C	56 bar @ 20C
Temperature (°C)	-20 - +60	-20 - +60	-20 - +60	-20 - +60
Cylinder material	Stainless steel	Stainless steel	Aluminium	Aluminium
Pressurising gas	Nitrogen	Nitrogen	-	-

checkfire!

# Cherwell Fire Safety

## Water Extinguishers

FirePower is an industry-recognised and respected brand that offers a wide selection of quality extinguishers.

The range includes both stored-pressure and cartridge-operated units, with a choice of Water, Foam, Powder and CO<sub>2</sub> for use on almost every type of fire.

### Water



### Stored Pressure/ Cartridge Operated

Water extinguishers are still one of the most cost-effective ways to put out free-burning material fires such as paper, wood and fabrics.

- Kitemarked to BS EN3
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Protective plastic base
- Complete with bracket
- Marine approved (FW9C)



### Specification

Type	Water S/P	Water C/O
Capacity (ltr)	9	9
Fire rating	21A	21A
Height (mm)	600	600
Cylinder diameter (mm)	189	189
Overall width (mm)	300	330
Filled Weight (kg)	14.18	14.87
Range of throw (m)	>4	>4
Duration of discharge (secs)	50	60
Working pressure (at 20°C)	15 bar	10 bar
Temperature (°C)	0 to 60	0 to 60
BS EN3 approved	Yes	Yes
MED approved		Yes
Part No:	FW9P	FW9C

# Foam Extinguishers

## Foam

Spray foam extinguishers provide a fast, powerful means of tackling flammable liquid fires. The foam forms a seal over the surface to prevent re-ignition.

### Stored Pressure



- Kitemarked to BS EN3
- Spray nozzle
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Protective plastic base\*
- Complete with bracket
- 6ltr and 9ltr models have passed the 35kv conductivity discharge test

\* Excludes 2 ltr model

### Cartridge Operated



- Kitemarked to BS EN3
- Spray nozzle
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Protective plastic base
- Complete with bracket
- Branchpipe model is also suitable for alcohol risks
- 6 ltr and 9 ltr foam spray extinguishers have passed the 35kv conductivity discharge test
- Marine approved (FF6C and FF9C)

## Specifications

Type	AFFF Foam Spray S/P	AFFF Foam Spray S/P	AFFF Foam Spray S/P	AFFF Foam Spray C/O	AFFF Foam Spray C/O	FFFP-AR Spray Branchpipe C/O
Capacity (ltr)	2	6	9	6	9	9
Fire rating	8A 55B	13A 144B	21A 183B	13A 144B	21A 183B	21A 183B
Height (mm)	395	565	600	560	600	600
Cylinder diameter (mm)	112	160	189	160	189	189
Overall width (mm)	150	290	300	310	330	380
Filled Weight (kg)	3.81	10.09	14.21	10.67	15	15.1
Range of throw (m)	>2	>4	>4	>4	>4	>4
Duration of discharge (secs)	12	30	40	30	40	35
Working pressure (at 20°C)	15 bar	15 bar	15 bar	14 bar	10 bar	15 bar
Temperature (°C)	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60
BS EN3 approved	Yes	Yes	Yes	Yes	Yes	Yes
MED approved	-	-	-	-	Yes	Yes
Part No:	<b>FF2P</b>	<b>FF6P</b>	<b>FF9P</b>	<b>FF6C</b>	<b>FF9C</b>	<b>FFAR9C</b>

# CO<sub>2</sub> Extinguishers

## Cherwell Fire Safety



Harmless to electrical equipment. Both these CO<sub>2</sub> extinguishers have non-conductive anti-static horns.

- Squeeze grip operation
- Corrosion resistant finish
- Harmless to machinery
- Kitemarked to BS EN3
- Complete with bracket

### Specifications

Type	CO <sub>2</sub> Squat Aluminium	CO <sub>2</sub> Aluminium
Capacity (kg)	2	5
Fire rating	34B	70B
Height (mm)	490	750
Cylinder diameter (mm)	117	152
Overall width (mm)	180	310
Filled Weight (kg)	4.91	11.43
Range of throw (m)	>4	>4
Duration of discharge (secs)	8	14
Working pressure (at 20°C)	56 bar	56 bar
Temperature (°C)	-20 to 60	-20 to 60
BS EN3 approved	Yes	Yes
Part No:	FC2	FC5

### Water with Additive



The additive provides quicker flame knock-down compared to standard water extinguishers which allows units in smaller sizes and lighter weight but with improved fire-fighting capability.

- Kitemarked to BS EN3
- Lighter weight and more effective on Class A fires than normal water extinguishers
- Spray nozzle ensures wide coverage
- 15 bar working pressure
- Both models passed 35kv conductivity test
- Available in 3ltr and 6ltr capacity
- 1tr fire rating 13A Part No: FWA3
- 6ltr fire rating 21A Part No: FWA6

checkfire!

# Cherwell Fire Safety

## Powder Extinguishers

### Powder



### Stored Pressure



Dry Powder is a highly versatile medium for tackling most types of fires. Extremely effective on electrical hazards, flammable liquids and gases.



- Kitemarked to BS EN3
- Multi-purpose application
- Squeeze grip operation
- Corrosion resistant finish
- Protective plastic base\*
- Complete with bracket

\*Excludes 1kg and 2kg models.

### Powder



Budget priced ABC powder extinguishers.



- Kitemarked to BS EN3
- Multi-purpose application
- Squeeze grip operation
- Corrosion resistant finish
- Complete with bracket
- 1kg fire rating 8A-34B Part No. FP1B
- 2kg fire rating 13A-70B Part No. FP2B

### Specifications

Type	ABC	ABC	ABC	ABC	ABC
	Powder S/P		Powder S/P		Powder S/P
Capacity (kg)	1	2	4	6	9
Fire rating	8A 55B	13A 70B	21A 113B	34A 233B	43A 233B
Height (mm)	340	370	430	565	600
Cylinder diameter (mm)	80	112	160	160	189
Overall width (mm)	135	150	310	290	300
Filled Weight (kg)	1.67	3.62	6.98	9.62	14.37
Range of throw (m)	>2	>2	>4	>4	>4
Duration of discharge (secs)	9	10	12	15	15
Working pressure (at 20°C)	15 bar	15 bar	15 bar	15 bar	15 bar
Temperature (°C)	-30 to 60	-30 to 60	-30 to 60	-30 to 60	-30 to 60
BS EN3 approved	Yes	Yes	Yes	Yes	Yes
Part No:	<b>FP1</b>	<b>FP2</b>	<b>FP4</b>	<b>FP6</b>	<b>FP9</b>

# Wet Chemical Extinguisher

## Stored pressure



- Capable of extinguishing a cooking oil or fat fire of up to 75 litres in size
- 13A fire rating for all round safety and embraces the 35kV di-electric test
- EN3 red, with official canary yellow colour coding
- User-friendly 6 litre size - supplied factory filled
- Wet chemical process seals the surface of burning oil to prevent re-ignition
- Cylinder, lance and nozzle constructed from high quality stainless steel
- Unique hose swivel joint for ease of direction of discharge

## Specification

Type	Chemical Foam Spray S/P
Capacity (ltr)	6
Fire rating	13A 75F
Height (mm)	650
Cylinder diameter (mm)	180
Overall width (mm)	310
Filled Weight (kg)	11.03
Range of throw (m)	>2
Duration of discharge (secs)	48
Working pressure (at 20°C)	6.9 bar
Temperature (°C)	0 to 60
BS 7937 approved	Yes
MED approved	Yes
<b>Part No:</b>	<b>FWC6</b>

checkfire.

# Wheeled Extinguishers

## Powder



### Wheeled powder extinguishers



- Highly effective, with a fast flame knockdown
- Highly manoeuvrable
- Supplied filled
- Standard sizes 50kg and 100kg

## Specifications

Type	ABC Powder Cartridge	ABC Powder Cartridge
Capacity (kg - lt)	50	100
Cartridge (kg)	2	4
Cylinder diameter (mm)	300	360
Cylinder material	Steel DD12 uni en 10111	Steel DD12 uni en 10111
Wheels diameter (mm)	200	300
Hose length (m)	3.5	5
Extinguishant type	ABC 30	ABC 30
Weight (kg)	108	155
Volume x unit (m3)	0.35	0.5
Overall height (mm)	1070	1300
Throw length (m)	9	11
Operating pressure (bar)	15	15
Test pressure (bar)	26	26
Burst pressure (bar>)	55	55
Discharge time (secs)	50	90
<b>Part No:</b>	<b>WFP 50</b>	<b>WFP 100</b>

Note: Other models available on request but subject to lead times.

# Wheeled Extinguishers

CO<sub>2</sub>

## Wheeled CO<sub>2</sub> extinguishers



- Ideal for protecting large electrical risks
- Rapid fire control with minimum clean up
- Standard sizes 10kg and 20kg. Other sizes available on request

## Specifications

Type	Carbon Dioxide	Carbon Dioxide
Capacity (kg - lt)	10	20
Cylinder diameter (mm)	170	227
Cylinder material	35 cr Mo 4	35 cr Mo 4
Wheels diameter (mm)	200	300
Hose length (m)	1.0	3.5
Extinguishant type	CO <sub>2</sub>	CO <sub>2</sub>
Weight (kg)	36	67
Volume x unit (m <sup>3</sup> )	0.15	0.25
Overall height (mm)	1220	1400
Throw length (m)	6	6.7
Operating pressure (bar)	60	60
Test pressure (bar)	250	250
Burst pressure (bar>)	450	450
Discharge time (secs)	15	30
<b>Part No:</b>	<b>WFC 10</b>	<b>WFC 20</b>

Note: Other models available on request but subject to lead times.

# Wheeled Extinguishers

## Foam



### Wheeled Foam extinguishers



- Highly effective Aqueous Film Forming Foam (AFFF)
- Supplied empty with a foam charge
- Standard sizes 50 litres and 100 litres

## Specifications

Type	Foam	Foam
Capacity (kg - lt)	50	100
Cartridge (kg)	2	4
Cylinder diameter (mm)	300	400
Cylinder material	Stainless Steel	Stainless Steel
Wheels diameter (mm)	200	300
Hose length (m)	5	5
Extinguishant type	Sealfire®AFFF	Sealfire®AFFF
Weight (kg)	89	148
Volume x unit (m3)	0.35	0.6
Overall height (mm)	1100	1360
Throw length (m)	10	10
Operating pressure (bar)	15	15
Test pressure (bar)	26	26
Burst pressure (bar>)	55	55
Discharge time (secs)	60	90
<b>Part No:</b>	<b>WFF 50</b>	<b>WFF 100</b>

Note: Other models available on request but subject to lead times.

# Renovated Extinguishers

CO<sub>2</sub> painted



## CO<sub>2</sub> Extinguishers

- Range of fully renovated 2kg and 5kg CO<sub>2</sub> extinguishers
- All renovated CO<sub>2</sub> cylinders come complete with new valve and dip tube
- High quality finish

Part Nos: 2kg - REC200A  
5kg - REC500A

CO<sub>2</sub> polished



## Polished Renovated CO<sub>2</sub> Extinguishers

- Aluminium 2kg and 5kg CO<sub>2</sub> cylinders with superb polished finish suitable for prestige developments
- All units supplied with new valve and dip tube

Part Nos: 2kg - RECP200  
5kg - RECP500

# Hose Reels

## Cherwell Fire Safety

### Fixed reels



- Accommodates 30m of 19mm or 25mm hose tubing
- Jet Spray nozzle included in all models
- Available in Automatic or Manual
- Easy to install and maintain
- High quality powder coated finish

**HR1** – 19mm Fixed Manual Reel

**HR2** – 25mm Fixed Manual Reel

**HR3** – 19mm Fixed Automatic Reel

**HR4** – 25mm Fixed Automatic Reel

### Swinging reels



- Accommodates 30m of 19mm or 25mm hose tubing
- Jet Spray nozzle included in all models
- Available in Automatic or Manual
- Easy to install and maintain
- High quality powder coated finish

**HR5** – 19mm Swinging Manual Reel

**HR6** – 25mm Swinging Manual Reel

**HR7** – 19mm Swinging Automatic Reel

**HR8** – 25mm Swinging Automatic Reel

### HR9



PVC Hose Reel Cover.

checkfire.

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

# Fire Blankets

## Cherwell Fire Safety

A full range of top quality fire blankets available

- All blankets conform to BS EN 1869: 1997
- Unique 3 ply material
- Rigid, attractive wipe clean packs

### Specification



The most popular sizes as follows:

- FB01** – 1.1m x 1.1m
- FB02** – 1.2m x 1.2m
- FB03** – 1.8m x 1.2m
- FB04** – 1.75 x 1.75

Also available – a wide range of welding drapes.  
Please contact our sales office for details.

### Welding drapes



checkfire.